



NO	Name	Material	Finish	QTY
1	ANTENNA TOP COVER	PC	BLACK	1
2	ANTENNA Bottom Cover	PC	BLACK	1
3	RG174 Cable loss	PVC	BLACK	2
4	LTE Antenna	FR4	BLACK	1
5	GPS			1
6	Adesive Heat shrink 3.2*15	PE	BLACK	2
7	Heat shrink(4*20)Print	PE	WHITE	2
8	Adesive Heat shrink 6*30	PE	BLACK	2
9	NUT M12*1.0P	BRASS	NI	1
10	WASHER	FE	NI	1
11	SMA MALE FOR LTE	BRASS	GOLD	1
12	RP-SMA MALE FOR GPS	BRASS	GOLD	1
13	O-RING			1
14	Rubber			1
15	M3*10 NUT	FE	BLACK	4
16	TUPE	PET	BLACK	1

Electrical Properties	
Frequency Range	L1:700~2700MHZ L2:1575.42MHZ
Impedance	50 Ω
V.S.W.R.	L1≤3.0 L2≤2.0
Radiation	Omni
Gain	L1:3.0DBi L2:28DBi
Polarization	Vertical
Mechanical Properties	
Whip	PC
Standard Connector	SMA
Waterproof Level	IP68
Operating Temp	-40°~ +105°

THIRD ANGLE PROJECTION  Tolerance .X ±0.1 .XX ±0.05 .x ±1°	DRAWN BY	HZH	MATERIAL:		PART NO:	M530. M3. 2. 333
	CHECKED BY		FINISH:		TITLE:	LTE GPS 2 in 1 Antenna
	APPROVED BY	King	UNIT:	mm	 <b>RUNSHUN</b> Dongguan RunShun /www.rsantenna.com	
	DATE:	21. 1. 23	SCALE:	1/1		