



NO	Name	Material	Finish	QTY
1	ANTENNA TOP COVER	PC	BLACK	1
2	ANTENNA Bottom Cover	PC	BLACK	1
3	RG174 Cable loss	PVC	BLACK	2
4	GPS Antenna		Yellow	1
5	Heat shrink 3.2*15	PE	BLACK	1
6	shrink Tube(4*20)Print	PE	Yellow	1
7	NUT M12*1.0P	BRASS	NI	1
8	WASHER	FE	NI	1
9	SMA MALE	BRASS	GOLD	1
10	O-RING			1
11	Rubber			1
12	M3*10 NUT	FE	BLACK	4

Electrical Properties	
Frequency Range	1575.42~1602MHZ
Impedance	50 Ω
V.S.W.R.	≤2.0
Radiation	Omni
Gain	28 DBi
Polarization	Vertical
Mechanical Properties	
Whip	PC
Standard Connector	SMA MALE
Waterproof Level	IP68
Operating Temp	-40°~ +105°

THIRD ANGLE PROJECTION



Tolerance  
 .X ±0.1  
 .XX ±0.05  
 .x ±1°

DRAWN BY	HZH	MATERIAL:		PART NO:	M530. S1. 1. 333
CHECKED BY		FINISH:		TITLE:	M530 GPS+GLONASS Antenna
APPROVED BY	King	UNIT:	mm	 Dongguan RunShun /www.rsantenna.com	
DATE:	21.6.3	SCALE:	1/1		