



Electrical Properties	
Frequency Range	698~2700MHZ
Impedance	50 Ω
V.S.W.R.	LTE≤3.0
Radiation	Omni
Gain	4G:3.5dBi
Polarization	Vertical
Mechanical Properties	
Random	PC+ABS
Standard Connector	SMA MALE
Waterproof Level	IP65
Operating Temp	-40°~ +80°

NO	Name	Material	Finish	QTY
1	SMA Male	Brass	GOLD	1
2	CFD100 CABLE	PVC	BLACK	1
3	Housing	PC/ABS	BLACK	1
4	Antenna	FR4	BLACK	1
5	Magnetic	NdFeB	NI	1
6	Sticker	PC	BLACK	1
7	NUT	Brass	NI	1
8	Shrink Tube	PE	BLACK	1

THIRD ANGLE PROJECTION Tolerance .X ±0.1 .XX ±0.05 .x ±1°	DRAWN BY	HZH	MATERIAL:		PART NO:	M902. C1. 1. 334
	CHECKED BY		FINISH:		TITLE:	4G/LTE Magnetic Antenna
	APPROVED BY	King	UNIT:	mm	RUNSHUN Dongguan RunShun /www.rsantenna.com	
	DATE:	20. 8. 22	SCALE:	1/1		