



Electrical Properties	
Frequency Range	698~2700MHZ
Impedance	1575.42~1602MHZ
V.S.W.R.	50 Ω
	LTE≤2.5
	GPS≤2.0
Radiation	Omni
Gain	4G:5.0dBi
Polarization	GPS:28dBi
	Vertical
Mechanical Properties	
Random	PC+ABS
Standard Connector	SMA(M)/RP-SMA(M)
Operating Temp	-40°~+85°

NO	Name	Material	Finish	QTY
1	SMA Male (LTE)	Brass	GOLD	1
2	CFD200 CABLE (LTE)	PVC	BLACK	1
3	RP-SMA Male (GPS)	Brass	GOLD	1
4	RG174 CABLE (GPS)	PVC	BLACK	1
5	3M VHB Glue		RED	1
6	Housing	PC/ABS	BLACK	1
7	LTE Antenna	FR4	BLACK	1
8	GPS Antenna			1
9	NUT	Brass	NI	1
10	Shrink Tube (print LTE)	PE	Blue	1
11	Shrink Tube (print GPS)	PE	Yellow	1
12	Tube	PET	BLACK	1
13				

THIRD ANGLE PROJECTION  Tolerance .X ±0.1 .XX ±0.05 .x ±1°	DRAWN BY	HZH	MATERIAL:		PART NO:	M902. M2. 2. 334
	CHECKED BY		FINISH:		TITLE:	M902 2 IN 1 Antenna
	APPROVED BY	King	UNIT:	mm	 RUNSHUN Dongguan RunShun /www.rsantenna.com	
	DATE:	20. 8. 22	SCALE:	1/1		