


3PCS /PE BAG (6\*9CM)




Electrical Properties	
Frequency Range	698-2700MHZ
Impedance	50 Ω
V.S.W.R.	700~960MHz≤4.0 1427.9~1462.9≤4.0 1710~2700MHz≤3.5
Radiation	Omni
Gain	3.5DBi
Polarization	Vertical
Mechanical Properties	
Whip	ABS
Standard Connector	SMA(Male)
Weight	- g(est)
Operating Temp	-40°~ +80°

BOM

NO	Name	Material	Finish	QTY
1	Top	ABS	BLACK	1
2	Bottom	ABS	BLACK	1
3	CFD100 Coaxial cable	FEP	BLACK	1
4	SMA Male	Brass C3604	Gold 1.5U"	1
5	Heat shrink Tube	PE	White	1
6	Antenna	FR4	BLACK	1
7	SCREW3*10		BLACK	4
8	3M Adhesive		RED	1
9	SCREW4*22	SUS		3
10	Cable SR	PVC	BLACK	1

THIRD ANGLE PROJECTION



Tolerance  
 .X ±0.1  
 .XX ±0.05  
 .x ±1°

DRAWN BY	li	MATERIAL:		PART NO:	M911.C1.1.333
CHECKED BY		FINISH:	BLACK	TITLE:	M911 LTE Antenna
APPROVED BY	King	UNIT:	mm		
DATE:	20.3.31	SCALE:	1/1		

**RS RUNSHUN**  
 Dongguan RunShun /www.rsantenna.com