



Electrical Properties	
Frequency Range	698~2700MHZ 1575.42MHZ
Impedance	50 Ω
V.S.W.R.	LTE:≤3.5 GPS≤2.0
Radiation	Omni
Gain	LTE:3.0DBI GPS:28DBI
Polarization	Vertical
Mechanical Properties	
Whip	PC+PBT
Standard Connector	SMA MALE
Waterprooflevel	N.A
Operating Temp	-φ40°~ +80°

7	Antenna		2
6	CABLE SR	PVC BLACK	1
5	Hot Shrink Tube	PE	2
4	3M Glue	VHB	1
3	SMA CONNECTOR	GOLD	2
2	RG174 CABLE	PVC BLACK	2
1	ANTENNA COVE	PC+PBT BLACK	1
	Description	Material	Q'ty

THIRD ANGLE  
PROJECTION



Tolerance  
.X ±0.1  
.XX ±0.05  
.x ±1°

DRAWN BY	HZH	MATERIAL:		PART NO:	P776.M2.2.333
CHECKED BY		FINISH:	BLACK	TITLE:	P776 2 IN 1 Antenna
APPROVED BY	King	UNIT:	mm	 Dongguan RunShun /www.rsantenna.com	
DATE:	20.10.14	SCALE:	1/1		