



| Electrical Properties | |
|-----------------------|----------------|
| Frequency Range | 698MHZ~2700MHZ |
| Impedance | 50 Ω |
| V.S.W.R. | ≤2.0 |
| Radiation | Omni |
| Gain | 6dBi±0.5 |
| Polarization | Vertical |
| Mechanical Properties | |
| Whip | ABS |
| Standard Connector | SMA MALE |
| Weight | - 65g(est) |
| Operating Temp | -40~+85 |

| NO | Name | Material | Finish | QTY |
|----|------------------|----------|--------|-----|
| 1 | SMA MALE | Brass | GOLD | 1 |
| 2 | RG174 CABLE | PVC | BLACK | 1 |
| 3 | Stickers | PVC | BLACK | 1 |
| 4 | Magnet | NdFeB | Silver | 1 |
| 5 | Magnet Cover | FE | Silver | 1 |
| 6 | Base | ABS | Black | 1 |
| 7 | Connecting shaft | BRASS | NI | 1 |
| 8 | Antenna | FE | BLACK | 1 |
| 9 | Shrink tube | PE | BLACK | 1 |

| | | | | | | |
|----------------------------|-------------|-------|-----------|--------|---|------------------|
| THIRD ANGLE PROJECTION | DRAWN BY | li | MATERIAL: | | PART NO: | X045. C1. 1. 333 |
| | CHECKED BY | | FINISH: | BLACK | TITLE: | 3G/4G ANTENNA |
| | APPROVED BY | King | UNIT: | mm | RUNSHUN Dongguan Run Shun Technology CO., Ltd | |
| Tolerance | | DATE: | 19. 1. 11 | SCALE: | | |
| . X | ±0.1 | | | | | |
| . XX | ±0.05 | | | | | |
| . x | ±1° | | | | | |