

1/4-36UNEF-2B


Electrical Properties

Frequency Range	698~2700MHZ
Impedance	50 Ω
V.S.W.R.	≤3.0
Radiation	Omni
Gain	3.0DBi
Polarization	Vertical
Mechanical Properties	
Whip	TPEE
Standard Connector	SMA Male
Weight	- g(est)
Operating Temp	-40°~ +85°


BOM

NO	Name	Material	Finish	QTY
1	Top	TPEE	Black	1
2	RG 174 Coaxial cable	PVC	Black	1
3	SMA Connector	Brass	Gold	1
4	Shrink tube	PE	BLACK	1
5	Antenna	Brass		1
6	sticker	PVC	BLACK	1
7	Magnet	NdFeB	Silver	1
8	BASE	ABS	BLACK	1

THIRD ANGLE PROJECTION



Tolerance
 .X ±0.1
 .XX ±0.05
 .x ±1°

DRAWN BY	li	MATERIAL:		PART NO	X310.C1.1.331
CHECKED BY		FINISH:	Black	TITLE:	LTE ANTENNA
APPROVED BY	King	UNIT:	mm	 RUNSHUN Dongguan RuhShun/www.rsantenna.com	
DATE:	20.7.17	SCALE:	1/1		