



| Electrical Properties |                                |
|-----------------------|--------------------------------|
| Frequency Range       | 2*698~6000MHz                  |
| Impedance             | 50 $\Omega$                    |
| V.S.W.R.              | $\leq 2.5$                     |
| Radiation             | Omni                           |
| Gain                  | 5.0dBi                         |
| Polarization          | Vertical                       |
| Mechanical Properties |                                |
| Material              | PC+ABS                         |
| Standard Connector    | SMA Male                       |
| Waterproof Level      | IP68                           |
| Operating Temp        | -40 $^{\circ}$ ~+80 $^{\circ}$ |

| NO | Name                 | Material | Finish | QTY |
|----|----------------------|----------|--------|-----|
| 1  | ANTENNA COVER        | PC+ABS   | BLACK  | 1   |
| 2  | ANTENNA Bottom Cover | PC+ABS   | BLACK  | 1   |
| 3  | NUT                  | BRASS    | NI     | 1   |
| 4  | CFD200 Cable         | PVC      | BLACK  | 2   |
| 5  | SMA MALE             | Brass    | Gold   | 2   |
| 6  | Shrink tube          | PE       | Blue   | 2   |
| 7  | TUBE                 | PET      | BLACK  | 1   |
| 8  |                      |          |        |     |

|  |             |         |           |     |   |                      |
|--|-------------|---------|-----------|-----|---|----------------------|
| THIRD ANGLE<br>PROJECTION<br><br>Tolerance<br>.X $\pm 0.1$<br>.XX $\pm 0.05$<br>.x $\pm 1^{\circ}$ | DRAWN BY    | HZH     | MATERIAL: |     | PART NO:  | M861.C2.2.339        |
|  | CHECKED BY  |         | FINISH:   |     | TITLE:  | 2*5G/4G MIMO Antenna |
|  | APPROVED BY | King    | UNIT:     | mm  | <br>Dongguan RunShun/www.rsantenna.com |                      |
|  | DATE:       | 20.5.10 | SCALE:    | 1/1 |   |                      |