



Electrical Properties	
Frequency Range	617~7125MHZ
Impedance	50 Ω
V.S.W.R.	≤3.0
Radiation	Omni
Gain	6.0DBi
Polarization	Vertical
Mechanical Properties	
Random	PC+ABS
Standard Connector	SMA Male
Waterproof Level	IP65
Operating Temp	-40°~ +85°

NO	Name	Material	Finish	QTY
1	Antenna Houshing	PC+ABS	BLACK	1
2	Antenna	FR4	BLACK	1
3	Magnetic BASE	FE	BLACK	1
4	NMO CONNECTOR	SUS304	N. A	1
5	SMA Male Connector	C3604	Gold	1
6	RG58 CABLE	PE	BLACK	1
7	Heat Shrink tuge	PE	BLACK	2
8	Ferrite Magnet	Ferrite	BLACK	1
9	Sticker	PVC	Black	1
10	Sticker	EVA	BLACK	1

THIRD ANGLE PROJECTION  Tolerance .X ±0.1 .XX ±0.05 .x ±1°	DRAWN BY	HZH	MATERIAL:		PART NO:	X820. C3. 1. 335
	CHECKED BY		FINISH:		TITLE:	NMO Car Antenna
	APPROVED BY	King	UNIT:	mm	 Dongguan RunShun/www.rsantenna.com	
	DATE:	22. 6. 6	SCALE:	1/1		